UV-Vis Spectrophotometer

Model **MSTQNVW7111USWISS** | Brand **Master Science** | Unit **Pc**



UV VIS Spectrophotometer MSTQNVW7111USWISS Key Features: Wavelength Range: 190-1100 nm Single Beam Design: Offers high accuracy with reliable readings. Data Output Port: USB, allowing for seamless data transfer and connectivity. Touchscreen: Equipped with a 7" touchscreen for easy operation. Built-in Storage: 32GB memory and Bluetooth support for network connectivity.

KEY HIGHLIGHTS

- Data Output Port
- Advanced Data Analysis
- Automatic Start-Up Verification
- Data Export

Request a Quotation
Contact us for pricing, configuration options and delivery details.

support@themsci.com
www.themsci.com

Scan to view online

Key Features

OFFERS HIGH ACCURACY WITH RELIABLE READINGS.

Data Output Port
USB, allowing for seamless data transfer and connectivity.

Advanced Data Analysis
Includes functions like photometric measurement, spectral scanning, multi-wavelength testing, and data printing.

Enhances stability by isolating the optical path from external vibrations.

Automatic Start-Up Verification
Ensures accuracy and reliability over long-term use.

Data Export
Allows data export to a USB for further analysis or reporting.

Technical Specifications

PARAMETER	SPECIFICATION
Wavelength Range190-1100 nm	
TouchscreenEquipped with a 7" touchscreen for easy operation.	
Built-in Storage32GB memory and Bluetooth support for network connectivity.	
Wavelength Range190-1100 nm	
Spectral Bandwidth2 nm	
Wavelength Accuracy±0.5 nm	

PARAMETER	SPECIFICATION
Stray Light0.05%T @ 220 nm, 360 nm	
Wavelength Repeatability≤0.1 nm	
Photometric Repeatability (Stability)±0.001 Abs/h @ 500 nm	
Photometric Repeatability (Photometric Range)0-200%T, -0.3-3.0 A, 0-9999 C	
Photometric Repeatability (Baseline Flatness)±0.001 Abs	
Photometric Repeatability (Noise)±0.005 Abs	
Photometric Repeatability (Display)800 x 480 touch screen	
Photometric Repeatability (Light Source)Tungsten Lamp & Deuterium Lamp	
±0.2T (0-100%T)	
±0.002 Abs (0-0.5 Abs)	
±0.004 Abs (0.5-1.0 Abs)	
≤0.05%T (0-100%T)	
0.001 Abs (0-0.5 Abs)	
0.002 Abs (0.5-1.0 Abs)	

Standard Accessories Included

- AC220V/50Hz or 110V/60Hz
- Detector: Silicon Photodiode
- Dimensions: 461 x 381 x 181 mm
- Weight: 22 kg
- Spectrophotometer - 1 set
- 1 cm Glass Cuvette - 4 pcs
- Power Cord - 1 pc
- User’s Manual - 1 pc
- 1 cm Quartz Cuvette - 2 pcs
- Dust Cover - 1 pc
- This UV VIS Spectrophotometer is designed to offer precise and reliable performance for various analytical applications. With advanced features, a durable optical system, and easy-to-use data management tools, it is an excellent choice for research and quality control.